

www.nts.com

Anaheim: 714.999.1616

Test Request Form: MIL-PRF GROUP B Inspection

Company: Date:

Address: NTS Quotation Number:

City: State: Postal Code: Purchase Order:

Country: Cage Code / MFR# PO Authorized Signature:

Contact: Phone: Email:

Part Number: Revision: Production Month & Year: Date Code:

Serial Numbers: Lot Number:

Please indicate the specification sheet samples will be tested to:

Submission is for DLA monthly/annual retention ITAR Requirement:

MIL-PRF-50884 Revision:Amendment:(default to latest revision/amendment unless otherwise specified)MIL-PRF-55110 Revision:Amendment:(default to latest revision/amendment unless otherwise specified)

Material Type: IPC-4101 / IPC-4103 / IPC-4204 / Board Type:

Adhesiveless Slash # required Slash # required Total Layers:

GROUP B Inspection testing to be performed (please check all applicable tests):

Rework Simulation

Submit (2) type 'A' coupons representing the typical component hole or actual production sample.

Moisture and Insulation Resistance

Submit (2) type 'E' coupons ("Y" conductor pattern) [Same coupons can be used for DWV]

Dielectric Withstanding Voltage

Submit (2) type 'E' coupons ("Y" conductor pattern) [Same coupons can be used for MIR]

Resistance to Solvents

Submit (3) production boards or coupon strips with ink or paint markings.

Surface Peel Strength

Submit a total of (8) type 'N' or 'P' coupons from a minimum of (2) different production lots (four each from two lots). COPPER SAMPLES ONLY. All surface finish plating or coatings should be chemically removed from specimens prior to test. [Type 3, foil lamination only]

Lot #1 ID: Lot #1 s/n(s):
Lot #2 ID: Lot #2 s/n(s):
Lot #3 ID: Lot #3 s/n(s):
Lot #4 ID: Lot #4 s/n(s):

Special Test Instructions/Comments:

Final Test Report:

All final test reports are uploaded to NTS LabInsight for secure customer retrieval. A Hard copy may be requested for an additional fee.